

# HORRY ELECTRIC COOPERATIVE, INC.

A Touchstone Energy<sup>®</sup> Cooperative   
The power of human connections

## Approved Meter Base List

1 Phase Meter Sockets	Cutler Hammer/Eaton	Milbank	Siemens/Talon	Durham/Square D/Midwest*
125 amp, with lay-in type lugs	UTRS111BCH UTRS101BCH	U7487-RL-QG-CAPL U8435-XL-TG-HSP	UAT111-0JCA UAT111-XGF	UHT-RS101B
200 amp, with lay-in type lugs	U92197CCCPLCH UTRS213C UHTRS213CE	U1980-XLT-QG-CAPL U3850-XL-QG U3850-XL-QG-SCPSA U3850-XL-TG-HSP-PL U1980-O-HSP U1980-O-KK-BL U1980-XL 7040-XL-TG-HSP 7040-DL-TG-KK-BLG	UAS917-XJCA UAS917-0G UAT777-XG UAS877-PG UAS877-PGF UAT417-XGDU	T-RS233C UT-RS223A UT-RS213 RC200S**
320 amp, with lever bypass, 3/8" studs on line and load side	UTH4300UCH UTH4300TCH UTH4300TFLCH	U1129-RXL U5740-X-K3L-K2L-CAPL U4367-X-K3L-K2L-SCPSA	47604-82 47604-02	T-H 4300U
400 amp Bolt-in, type K-4, with 1/2" studs on line and load side	CH8416K4	U4664-XT-9507	9809-8416	N/A
600 amp Bolt-in, type K-4, with 1/2" studs on line and load side	CH9507K4		9810-9507	

1 Phase Gang Sockets	Cutler Hammer/Eaton	Milbank	Siemens/Talon	Durham/Square D
2 position, with lay-in type lugs, 200amps/position, 200 amps overall ampacity	UT2R2332TCH	U1252-X-K1-CAPL	UA2717-YJCA	T-2R2332U
3 position, with lay-in type lugs, 200 amps/position, 270 amps overall ampacity	UT3R2332TCH	U1253-X-K1-CAPL	UA3717-YJCA	T-3R2332U
4 position, with lay-in type lugs, 200 amps/position, 360 amps overall ampacity	UT4R2352TCH	U1254-X-K1-CAPL	UA 4719-YJCA	T-4R2352U
5 position, with lay-in type lugs, 200 amps/position, 450 amps overall ampacity	UT5R2392TTCH	U1255-X-K1-CAPL	UA5719-KJCA	T-5R2392U
6 position, with lay-in type lugs, 200 amps/position, 528 amps overall ampacity	UT6R2392TTCH	U1256-X-K1-CAPL	UA6719-KJCA	T-6R2392U

3 Phase meter sockets	Cutler Hammer/Eaton	Milbank	Siemens/Talon	Durham/Square D
200 amp, with lever bypass, lay-in type lugs on line & load side	UTH7213TCH UTH7213UCH UTE7213UFLCH	U7423-RXL U4701-RXL U9701-X-QG-HSP	40407-025 40407-025F	T-H 7213V
200 amp, with lever bypass, 3/8" studs on line & load side	UTH7210UCH	U 9761-RRL	47607-01FL 42507-025	UT-H7230Z
320 amp, with lever bypass, 3/8" studs on line & load side	UTH7330UCH UTH7300TFLCH	U 2120-X U2594-X U3566-X-HSP	47407-02 49007-02FL	T-H 7330U
480 amp bolt-in, type K-7T, with 1/2" studs on line and load side		UA4667-XT-9504		N/A
600 amp bolt-in, type K-7T, with 1/2" studs on line and load side	CH9504K7		9817-9504	

Notes

\*These item numbers approved for Square-D, GE, and Midwest Electric Products with suffixes SQD, GE, or MEP

\*\*HEC maximum wire size will be 4/0

Revised 01/16/2025